

# ASXvOLT16

## Bare-Metal Hardware



### Product Overview

The ASXvOLT16 is a 16-10G-port XGS-PON virtual Optical Line Terminal (vOLT) with 4 x 100G/40G QSFP28 fixed ports. The 10G ports, 100G uplink ports, and console/management USB ports are all on the front panel. All 10G ports operate at wire-speed by default and support standard XGS-PON transceivers. The QSFP28 ports support 100G and 40G operation modes, as well as being configurable as 4 x 25GbE or 4 x 10 GbE modes using DAC breakout cables. This vOLT supports redundant hot-swappable PSUs and fans, and is available with a front-to-back or back-to-front airflow direction.

### Key Features and Benefits

- Cost-effective, bare-metal hardware for communication service providers.
- 4 x QSFP28 switch ports, each supporting 1 x 100 GbE or 1 x 40 GbE, or via breakout cables 2 x 50 GbE, 4 x 25 GbE, or 4 x 10 GbE.
- Layer 2 or Layer 3 forwarding at 300 Gbps (full duplex).
- Supports hot/cold aisles with front-to-back airflow SKU.
- All ports on front; PSUs and fans accessible from rear.
- Hot-swappable, load-sharing, redundant AC or -48V DC PSUs.
- 5+1 redundant, hot-swappable fan modules.
- Handles the abstraction between the protocol and the native hardware RPC.
- Bare-Metal hardware switch pre-loaded with diagnostics software and with Open Network Install Environment (ONIE) for automated loading of compatible open source and commercial NOS offerings.

## Features

### Ports

Switch Ports:

- 16 x XGS-PON ports
- 4 x QSFP28 100 GbE

Management ports on port side:

- 1 x RJ-45 serial console
- 1 x RJ-45 100/1000BASE-T management
- 1 x USB Type A storage

### Key Components

Switch Silicon: BCM88470 300 Gbps

CPU Modules:

- Intel Broadwell-DE XeonD-1518 2.2 GHz
- 8 GB x 2 SO-DIMM DDR4 RAM
- 16 MB SPI Flash (Boot)

### Performance

Switching Capability: 300 Gbps

Jumbo frames support up to 9 Kbytes

Packet Buffer Size: 32 K programmable wire-rate queues

### Physical and Environmental

Dimensions (WxDxH): 43.8 x 60.9 x 4.35 cm (17.3 x 23.9 x 1.7 in)

Weight: 10 kg (23 lb)

Fans: Hot-swappable 5 + 1 redundant fans

Operating Temperature: 5°C to 40°C (41°F to 104°F)

Storage Temperature: -40°C to 40°C (-40°F to 104°F)

Operating Humidity: 5% to 85% non-condensing

### LEDs

QSFP28 Port LEDs: Link Status, Activity, Rate

Ethernet Management Port LED: Link Status, Activity

System LEDs: Diagnostic, Locator, PSU and Fan Status

### Power

PSUs: 2 redundant, load-sharing, hot-swappable AC or 48 VDC\*

Input Voltage: 90 to 240 VAC at 50-60 Hz or -36 to -72 VDC

### Regulatory

EMI

CE Mark

EN55022 Class A

EN55024

EN61000-3-2

EN61000-3-3

FCC Part 15 Subpart B Class A

VCCI Class A

CCC

Safety

CB

UL/CU/NRTL

CCC

Environmental Compliance

Vibration: GR-63-CORE \*

Shock: GR-63-CORE, GR-1089-CORE \*

Acoustic Level: 78 dB sound power at 26°C

(\*Compliance. Certification to pay by request)

RoHS-6 Compliant

Electrical and Electronic Equipment (WEEE Directive 2002/96/EC)

\*Future Release

### Warranty

Please check [www.edge-core.com](http://www.edge-core.com) for the warranty terms in your country.

### For More Information

To find out more about Edgecore Networks Corporation products and solutions, visit [www.edge-core.com](http://www.edge-core.com).

### About Edgecore Networks Corporation

Edgecore Networks Corporation is in the business of providing innovative network solutions. In the service provider network, in the data center or in the cloud, Edgecore Networks Corporation delivers the software and systems that transform the way the world connects. Edgecore Networks Corporation serves customers and partners worldwide. Additional information can be found at [www.edge-core.com](http://www.edge-core.com).

Edgecore Networks Corporation is a subsidiary of Accton Technology Corporation, the leading network ODM company. The Edgecore data center switches are developed and manufactured by Accton.

To purchase Edgecore Networks solutions, please contact your Edgecore Networks Corporation representatives at +886-3-563-8888 (HQ) or +1 (877) 828-CORE (877-828-2673) or authorized resellers.

© Copyright 2019 Edgecore Networks Corporation. The information contained herein is subject to change without notice. This document is for informational purposes only and does not set forth any warranty, expressed or implied, concerning any equipment, equipment feature, or service offered by Edgecore Networks Corporation. Edgecore Networks Corporation shall not be liable for technical or editorial errors or omissions contained herein.

## Ordering Information

Model Number	CPU Module	PSU	Airflow	Region (power cord)
ASXvOLT16-O-F-US	Intel® Xeon® D-1518 Processor	Dual AC PSUs	port-to-power airflow	N. America
ASXvOLT16-O-F-JP	Intel® Xeon® D-1518 Processor	Dual AC PSUs	port-to-power airflow	Japan
ASXvOLT16-O-F-EU	Intel® Xeon® D-1518 Processor	Dual AC PSUs	port-to-power airflow	Europe
ASXvOLT16-O-F-UK	Intel® Xeon® D-1518 Processor	Dual AC PSUs	port-to-power airflow	UK
ASXvOLT16-O-F-CH	Intel® Xeon® D-1518 Processor	Dual AC PSUs	port-to-power airflow	China
ASXvOLT16-O-48V-F	Intel® Xeon® D-1518 Processor	Dual 48VDC PSUs	Port to power airflow	NA